

Dräger Polytron 3000

Fixed gas detector

The Dräger Polytron 3000 is an intrinsically safe gas detector for the continuous monitoring of more than 60 toxic gases and oxygen in ambient air. It is the part of a new generation of gas detectors developed on a modular platform. Communication to the central control system is done via a 4 to 20 mA signal.



ST-3826-2003

SIMPLE, QUICK INSTALLATION

The two component concept of a Docking Station and a Dräger Polytron 3000 electronics saves time and money. The Docking Station can be pre-installed – mounting and wiring it into place separately – while protected by a rain and dust cover until commissioning. At commissioning, the Dräger Polytron 3000 electronics is fixed by a quicklock mechanism into the Docking Station, the sensor inserted - and the system is ready for operation.

EASY TO OPERATE

The Dräger Polytron 3000 is easy to handle with simple maintenance procedures. The DrägerSensors are equipped with a data memory where the calibration information is stored. This allows the Dräger Polytron 3000 to either accept a precalibrated sensor, or the sensor can be calibrated with the transmitter. Digital temperature compensation of the sensor signal is automatically performed.

WIDE RANGE OF APPLICATION

With unsurpassed RFI resistance and versatile mounting options the Dräger Polytron 3000 is suitable for a wide range of applications.



ST-3811-2003

Dräger Polytron 3000
Intrinsically safe gas detector for toxic gases and oxygen in ambient air.

Gas

Ammonia	Boron Trichloride	Butadiene
Carbon Monoxide	Chlorine	Diborane
Diethyl Ether	Ethylene Oxide	Germane
Hydrazine	Hydrofluoric Acid	Hydrogen
Hydrogen Chloride	Hydrogen Cyanide	Hydrogen Sulfide
Isopropanol	Nitrogen Dioxide	Nitrogen Monoxide
Oxygen	Ozone	Phosphine
Propylene	Sulfur Dioxide	Tetrahydrofurane

For other gases ask our system centers

TECHNICAL DATA

Type	Intrinsically safe transmitter for electrochemical sensors		
Gases and Ranges	Toxic gases and oxygen in various ranges		
Output	Analog	4 to 20 mA	
	Maintenance signal	3.4 mA constant	
	Fault signal	< 3.2 mA	
Power Supply	12 to 30 VDC, 2-wire		
Ambient Conditions	Transmitter only, for sensors see separate sensor data sheet		
	Temperature	- 40 to + 65 °C / - 40 to + 150 °F	
	Pressure	700 to 1300 mbar / 20.7 to 38.4 inch Hg	
	Humidity	0 to 100 %RH, non condensing	
Enclosure	IP 66 / 67, NEMA 4, GRP housing, M20 cable gland		
Dimensions (approx.)	166 x 135 x 129 mm / 6.54" x 5.32" x 5.08" (H x W x D)		
Weight (approx.)	900 g / 2 lbs.		
Approvals	ATEX	II 1G EEx ia IIC T6/T4: - 40 to + 40 / + 65 °C	
		II 3G EEx nL IIC T6/T4: - 25 to + 40 / + 65 °C	
		II 3D IP6x T65 °C	
	IECEx	EEx ia IIC T6/T4: - 40 to + 40 / + 65 °C	
	UL	Class I, Div 1, Group A, B, C, D	
		Class II, Div 1, Group E, F, G T6/T4: - 40 to + 40 / + 65 °C	
	CSA	Class I, Div 1, Group A, B, C, D	
Ex ia T6/T4: - 40 to + 40 / + 65 °C			
CE mark	electromagnetic compatibility (directive 89/336/EEC)		

ORDER INFORMATION

Dräger Polytron 3000 with Display	Various
Dräger Polytron 3000 without Display	Various
Polytron Docking Station, one per transmitter	83 17 990
Duct Mount Kit	83 17 150

HEADQUARTERS:

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck, Germany

www.draeger.com

SYSTEM CENTERS:

P. R. CHINA

Beijing Fortune Draeger
Safety Equipment Co., Ltd.
Yu An Lu A 22, B Area
Beijing Tianzhu Airport
Industrial Zone
Houshayu Shunyi District
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

GERMANY

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck
Tel +49 451 882-2794
Fax +49 451 882-4991

FRANCE

Dräger Safety France SAS
3c route de la Fédération, BP 80141
67025 Strasbourg Cedex 1
Tel +33 3 88 40 59 29
Fax +33 3 88 40 76 67

SINGAPORE

Draeger Safety Asia Pte. Ltd.
67, Ayer Rajah Crescent # 06 03
139950 Singapore
Tel +65 68 72 92 88
Fax +65 67 73 20 33

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 544 475

USA

Draeger Safety, Inc.
505 Julie Rivers, Suite 150
Sugar Land, TX 77478
Tel +1 281 498 10 82
Fax +1 281 498 51 90